

High-End Satellite Receiver

- Professional-grade satellite receiver
- DVB-S2/S2X up to 256APSK and 72Mbaud
- High-quality reception and RF metrics

FEATURES

- Supports advanced DVB-S2(X) features: VCM, ACM, multiple input streams (MIS) and Generic Stream (GS).
- Decoding and analysis of DVB Carrier ID system (DVB-CID), even while satellite carrier is interfered with other carriers.
- Hardware demodulator can be bypassed to obtain I/Q samples for recording or for SDR-based demodulation software.
- Reception of BBFRAMES in L.3 packets.
- RF metrics and statistics are available for three windows (short, medium, long).
- LNB power insertion and DiSEqC support.
- Free SDK (DTAPI) for Windows and Linux is compatible with other DekTec adapters.
- PCI Express gen2 x4, low profile.



APPLICATIONS

- Monitoring solutions for DVB-S2 and S2X.
- DVB-CID monitoring and analysis.
- DVB-S2/S2X/CID modulator validation.
- High-speed data distribution.

KEY ATTRIBUTES

Parameter	Value	
RF input	75-Ω "F" female	
Input return loss	>15dB typical	
Tuning range	950 to 2150MHz	
Sensitivity	Typical	-80 to -20dBm
	Worst case	-60 to -20dBm
Symbol rate	0.09 to 72MBd	
Metrology	RF level	-80 to -20dBm
	MER	3 to 35dB
	Constellation	256 x 256
PCI-Express	PCIe2 x4 low profile	
OS	Windows	2k8/12/16,7,8,10
	Linux	≥2.6.32, 3.x, 4.x, 5.x

MODULATION STANDARDS

Modulation	Standard
DVB-CID	ETSI TS 103 129 v1.1.2*
DVB-S2	EN 302 307
DVB-S2X	EN 302 307-2

* Please check DekTec website for availability

ORDERING INFORMATION

Type	Description
DTA-2132	High-end satellite receiver for PCIe
DTA-2132-SX	DTA-2132 with <i>StreamXpert</i> [®]

The latest pricing information and a list of DekTec resellers can be found on dektec.com.