



# **All-Standard All-Band Modulator for USB-3**

- Modulator for all popular DTV standards
- ☐ Fully agile over VHF, UHF and L-band
- USB cable supplies power, data, control

#### **FEATURES**

- Pocket-size modulator for all popular satellite, cable and terrestrial standards
- Fully agile from 36 to 2150MHz, covering VHF, UHF and L-band
- Modulation bandwidth up to 70MHz
- Excellent signal quality
- Single USB cable to the DTU-315 supplies power, data and control
- Supports all constellations and modulation modes for each supported DTV standard
- Digital channel simulator option including multipath echo and AWGN insertion
- F and BNC cable assemblies included
- Use with DekTec's StreamXpress for easy generation of RF test signals
- own custom application



## **APPLICATIONS**

- RF test generator in your R&D lab or factory for developing, qualifying or repairing any equipment with a DTV antenna input
- Portable demo set for TV receivers, easy to carry to customer demos, trade shows, etc.
- Free Windows SDK (DTAPI) for writing your TV transmission or distribution using modulated signals in shops, hotels, hospitals etc.

#### **KEY ATTRIBUTES**

Value	
75-Ω micro-BNC female	
36 to 2150MHz	
70MHz	
0.08 to 70Msps	
-45 to -25dBm (0.5dB step	s)
>40dB	
<-105dBc @ 10kHz	
>50dB	
USB-3**	
Micro-B female	
Windows 7, 8/8.1, 10	
	75-Ω micro-BNC female 36 to 2150MHz 70MHz 0.08 to 70Msps -45 to -25dBm (0.5dB step) >40dB <-105dBc @ 10kHz >50dB USB-3** Micro-B female

<sup>\*</sup> For OFDM standards: up to 1GHz; for single-carrier standards up to 2GHz; above 2GHz the output level is max. 5dB lower.

#### **MODULATION STANDARDS**

L	Standards	
l	ADTB-T, ATSC, ATSC-M/H*, CMMB*, DAB(+)*,	
l	DMB-T/H*, DVB-C (QAM-A), DVB-C2*, DVB-S,	
l	DVB-S2, DVB-S2X*, DVB-T, DVB-T2 single-PLI	P,
l	DVB-T2*, I/Q samples*, ISDB-S*, ISDB-T*,	
l	QAM-B (J.83 Annex B), QAM-C, T-DMB*	

<sup>\*</sup> Option

### **ORDERING INFORMATION**

Туре	Description	
DTU-315-SP	All-standard all-band modula for USB-3 with <i>StreamXpress</i> player/test-generator softwar	
DTU-315-GOLD	DTU-315 with all current and future modulation options	I
DTR-315-RACK	1U 19"-rack mounting kit for holding up to 8x DTU-315	

Please refer to dektec.com for the latest pricing of the DTU-315 and its options, and for a list of distributors and resellers.

<sup>\*\*</sup> Must be a real USB-3 port; the DTU-315 will not operate with USB-2.